MATERIAL SAFETY DATA SHEET

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

LUBRIPLATE® Lubricants Co. 129 Lockwood St. Newark, NJ 07105 Emergency Telephone Number: 1-800-255-3924-CHEM-TEL (24 hour) Telephone Number for information: 1-973-589-9150

SUBSTANCE: LUBRIPLATE 930-AAA

TRADE NAMES/SYNONYMS:

PRODUCT USE: Petroleum lubricating grease

CREATION DATE: 10/23/2007 **REVISION DATE:** 02/26/2009

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT: Heavy hydrotreated naphthenic distillates (petroleum) CAS NUMBER: 64742-52-5 EC NUMBER (EINECS): 265-155-0 PERCENTAGE: 80-85

COMPONENT: Alkyl quaternary ammonium bentonite CAS NUMBER: 71011-25-1 EC NUMBER (EINECS): 275-125-9 PERCENTAGE: 6-10

COMPONENT: Zinc oxide CAS NUMBER: 1314-13-2 EC NUMBER (EINECS): 215-222-5 PERCENTAGE: 5-10

COMPONENT: Sulphurized fatty oil CAS NUMBER: 68991-19-5 EC NUMBER (EINECS): 273-639-8 PERCENTAGE: 2-5

NOTE: The IP 346 value of the mineral oil is less than 3%

SECTION 3 HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS: INHALATION:

SHORT TERM EXPOSURE: Irritation LONG TERM EXPOSURE: Lung damage SKIN CONTACT: SHORT TERM EXPOSURE: Irritation LONG TERM EXPOSURE: Irritation, skin disorders EYE CONTACT: SHORT TERM EXPOSURE: Irritation LONG TERM EXPOSURE: Information available INGESTION: SHORT TERM EXPOSURE: Diarrhea, difficulty breathing LONG TERM EXPOSURE: no information on significant adverse effects

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS): Health – 1 Flammability – 1 Reactivity – 0

Not a Controlled Product under (WHMIS) - Canada

SECTION 4 FIRST AID MEASURES

INHALATION: Vapor pressure is very low and inhalation at room temperature is not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash with soap and warm water. If injected by high pressure under skin, regardless of the appearance or its size, contact a physician IMMEDIATELY. Delay may cause loss of affected part of the body.

EYE CONTACT: Flush with clear water for 15 minutes or until irritation subsides. If irritation persists, consult a physician.

INGESTION: If ingested, call a physician immediately. Do not induce vomiting.

SECTION 5 FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Slight fire hazard

EXTINGUISHING MEDIA: Foam, Dry Chemical, Carbon Dioxide or Water Spray (Fog)

SPECIAL FIRE FIGHTING PROCEDURES: Cool exposed containers with water. Use air-supplied breathing equipment for enclosed or confined spaces.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not store or mix with strong oxidants. Empty containers retain residue. Do not cut, drill, grind, or weld, as they may explode.

Special Protection: See Section 8

SECTION 6 ACCIDENTAL RELEASE MEASURES

OCCUPATIONAL RELEASE: Scrape up grease, wash remainder with suitable petroleum solvent or add absorbent. Keep petroleum products out of sewers and water courses. Advise authorities if product has entered or may enter sewers and water courses.

SECTION 7 HANDLING AND STORAGE

STORAGE: Keep containers closed when not in use. Do not handle or store near heat, sparks, flame, or strong oxidants.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS: OIL MIST IN AIR (Not Encountered in Normal Usage): $5 \text{ mg/m}^3 \text{ UK OES TWA}$ $10 \text{mg/m}^3 \text{ UK OES STEL}$

VENTILATION: Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

EYE PROTECTION: Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

CLOTHING: Wear appropriate chemical resistant clothing.

GLOVES: Wear appropriate chemical resistant (nitrile) gloves.

RESPIRATOR: Consider the need for appropriate protective equipment, such as self-contained breathing apparatus, adequate masks and filters.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: semi-solid APPEARANCE: smooth COLOUR: off-white PHYSICAL FORM: grease ODOR: mineral oil odor BOILING POINT: >288 C FREEZING POINT: Not available FLASH POINT: 204 C (COC) LOWER FLAMMABLE LIMIT: 0.9% by volume UPPER FLAMMABLE LIMIT: 7.0% by volume AUTO IGNITION: not available VAPOUR PRESSURE: <0.01 mm Hg VAPOR DENSITY (air=1): >5 SPECIFIC GRAVITY (water=1): 0.95 DENSITY: not available WATER SOLUBILITY: negligible pH: not available VOLATILITY: not available ODOR THRESHOLD: not available EVAPORATION RATE (Butyl acetate = 1): <0.01 VISCOSITY: not available COEFFICIENT OF WATER/OIL DISTRIBUTION: not available

SECTION 10 STABILITY AND REACTIVITY

REACTIVITY: Stable at normal temperatures and pressures

CONDITIONS TO AVOID: Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

INCOMPATIBLES: Oxidising materials, chlorine

HAZARDOUS DECOMPOSITION: Thermal decomposition products or combustion: oxides of carbon, oxides of sulphur

POLYMERISATION: Will not polymerise.

SECTION 11 TOXICOLOGICAL INFORMATION

Heavy hydrotreated naphthenic distillates (petroleum): TOXICITY DATA: Low order of dermal and oral toxicity

Alkyl quaternary ammonium bentonite: TOXICITY DATA: No data available

Zinc oxide: TOXICITY DATA: No data available

Sulphurized fatty oil: TOXICITY DATA: No data available

SECTION 12 ECOLOGICAL INFORMATION

Not available

SECTION 13 DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable regulations

SECTION 14 TRANSPORT INFORMATION

LAND TRANSPORT ADR: No classification assigned.

LAND TRANSPORT RID: No classification assigned.

AIR TRANSPORT IATA: No classification assigned.

AIR TRANSPORT ICAO: No classification assigned.

MARITIME TRANSPORT IMDG: No classification assigned.

SECTION 15 REGULATORY INFORMATION

EUROPEAN REGULATIONS: EC CLASSIFICATION (CALCULATED): Not classified as dangerous.

SARA/TITLE III, Section 313 Status – Zinc compounds <8%

SECTION 16 OTHER INFORMATION

The above information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of LUBRIPLATE Lubricants Company. The data on these sheets relates only to the specific material designated herein. LUBRIPLATE Lubricants Company assumes no legal responsibility for use or reliance upon this data.