



Revision Number: 005.1

Issue date: 03/08/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE LB 8008 C5-A known as C5-A® Copper Based Anti-Seize
Product type: Lubricant
Restriction of Use: None identified
Company address: Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 234263
Item number: 51147
Region: United States
Contact information:
 Telephone: (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
------------------------	------------	-------------

Calcium dihydroxide	1305-62-0	10 - 20
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	10 - 20
Petroleum distillates, hydrotreated, light naphthenic	64742-53-6	10 - 20
Copper	7440-50-8	10 - 20
Graphite	7782-42-5	5 - 10
Quartz (SiO ₂)	14808-60-7	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Wash with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	None
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow material to contaminate ground water system.
Clean-up methods:	Scrape up as much material as possible. Clean residue with soap and water.

7. HANDLING AND STORAGE

Handling:	Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep container closed. Wash thoroughly after handling.
Storage:	Keep in a cool, well ventilated area.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Calcium dihydroxide	5 mg/m3 TWA	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA Inhalable fraction. 5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Petroleum distillates, hydrotreated, light naphthenic	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist. 500 ppm (2,000 mg/m3) PEL	None	None
Copper	0.2 mg/m3 TWA (as Cu) Fume. 1 mg/m3 TWA (as Cu) Dust and mist.	1 mg/m3 PEL (as Cu) Dust and mist. 0.1 mg/m3 PEL (as Cu) Fume.	None	None
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA	None	None
Quartz (SiO ₂)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust.	None	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Paste

Color:

Copper

Odor:

Mild

Odor threshold:

Not available.

pH:

Not applicable

Vapor pressure:

< 5.0 mm hg

Boiling point/range:

> 260 °C (> 500°F)

Melting point/ range:

Not available.

Specific gravity:

1.30

Vapor density:

Heavier than air.

Flash point:

> 93 °C (> 199.4 °F)

Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Autoignition temperature:	Not determined
Flammability:	Not applicable
Evaporation rate:	Slower than ether.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
VOC content:	< 3 % Estimated
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Hydrocarbons. Oxides of carbon.
Incompatible materials:	Strong acids and strong bases. Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Prolonged exposure to heat.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Inhalation of copper fumes may result in metal fume fever. Symptoms include metallic taste, discoloration of skin or hair. May cause respiratory tract irritation. Contains crystalline silica (quartz), which is classified as a possible carcinogen. However, the crystalline silica present in this product is encapsulated in the liquid and will only be liberated if the product is sanded or abraded, and even then what is liberated will not be pure crystalline silica. Appropriate precautions, however, should be taken if the product is sanded or abraded to prevent personnel from breathing the dust.

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye damage.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Calcium dihydroxide	Oral LD50 (Rat) = 7,340 mg/kg	Irritant, Corrosive
Distillates (petroleum), hydrotreated heavy naphthenic	None	Irritant
Petroleum distillates, hydrotreated, light naphthenic	None	Irritant
Copper	None	Allergen, Blood, Central nervous system, Developmental, Gastrointestinal, Immune system, Irritant, Kidney, Liver, Mutagen, Sensory, Skin
Graphite	None	Lung
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Calcium dihydroxide	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Petroleum distillates, hydrotreated, light naphthenic	No	No	No
Copper	No	No	No
Graphite	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Copper)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III
Marine pollutant: Copper
DOT Hazardous Substance(s): Copper

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.
Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Copper)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III
Marine pollutant: Copper

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Copper (CAS# 7440-50-8).
CERCLA Reportable quantity: Copper (CAS# 7440-50-8) 5,000 lbs. (2,270 kg)
California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Timothy Pratt, Regulatory Affairs Specialist

Issue date: 03/08/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.