

MATERIAL SAFETY DATA SHEET

Product:	765-1393	<i>Note: The information herein is given in good faith. No warranty, expressed or implied, is made.</i>	
Printed:			
Printed For:			
Original Issue Date:	11/12/85	Approved By:	Chuck Hiddema
Revision No. 3 Date:	07/25/01		V.P. Technical Operations
Section I - Identification			
Manufacturer:	AGS Company		
Street Address:	2651 Hoyt St		
City/State/Zip	Muskegon Hts., MI 49444		
Phone:	800-253-0403		
Phone:	231-733-2101		
FAX:	231-733-1784		
Transportation Emergency:	CHEM-TEL		
Phone:	800-255-3924		
Trade Name:	NAPA Lith-Ease Grease		
Catalog No.:	765-1393		
Common Name:	Lith-Ease		
Container/Size:	1 pound plastic tub		
NFPA - Health:	0		
Flammability:	1		
Reactivity:	0		
Specific Hazard:			
HMIS - Health:	0		
Flammability:	1		
Reactivity:	0		
Protective Equipment:	A		
Section II - Hazardous Ingredients			
Hazardous Ingredient	CAS No.	Wgt. %	TLV
1 White Lithium Grease	Not Assigned	100%	5 cu. m.
2			
3			
4			
5			
6			
7			
8			
9			
10			
NOTES:			

Section III Physical Data		Catalog No. 765-1393
pH - Supplied:	Not Applicable	
pH - Diluted:	Not Applicable	
Water Solubility:	Nil	
Specific Gravity:	(Water=1) 0.90	
Melting Point:	360°F (min.)	
Boiling Point:	Not Determined	
% Volatiles:	Not Applicable	
Vapor Pressure:	Not Applicable	
Vapor Density:	Not Applicable	
Evaporation Rate:	Not Applicable	
Appearance:	Pale yellow semi-solid with mineral oil odor.	
Section IV Fire & Explosion Data		
Flash Point:	> 400°F.	
Method:	C.O.C.	
Auto Ignition Temperature:	Not Determined	
Flammable Limits In Air	LEL: Not Determined	
	UEL: Not Determined	
Extinguishing Media:	Dry chemical, carbon dioxide, foam, water fog, sand or earth.	
Special Procedures:	Wear self-contained breathing apparatus.	
Unusual Hazards:	Dense smoke.	
Section V - Reactivity Data		
Unstable and/or Auto Reactive:	Stable	
Incompatible Materials:	Strong oxidizing agents.	
Hazardous Decomposition Products:	CO and carbon dioxide.	
Section VI - Emergency First Aid		
Eyes:	Flush with water for at least 15 minutes. Call physician immediately.	
Skin:	Wash thoroughly with soap & water.	
Ingestion:	Do not induce vomiting. Call physician immediately.	
Inhalation:	Of oil mist from grease; remove victim to fresh air. Administer oxygen or artificial respiration as required. Consult physician.	
Section VII - Health Effects		
Eyes:	May cause irritation.	
Skin:	May cause irritation on prolonged or repeated contact.	
Ingestion:	Contains petroleum, may cause diarrhea and nausea.	
Inhalation:	When at elevated temperature or aerosolized, may cause irritation of the respiratory tract.	
Other Effects:	Not known.	

Section VIII - Ventilation and Protective Measures		Catalog No. 765-1393
Ventilation Requirement:	General exhaust acceptable where a TLV of 5 cu. M. as mineral oil will not be exceeded.	
Eyes:	Yes	
Gloves:	Yes	
Clothing:	No	
Respiratory:	No	
Other:	Eye wash in work area.	
Section IX - Storage and Handling Procedures		
Conditions to Avoid:	None listed.	
Section X - Spill Procedures and Waste Disposal		
Spill Procedure:	Transfer bulk material to a container. Remove the residue with an absorbent material.	
Disposal Method:	Removal by an approved, licensed waste hauler.	
EPA Waste I.D. NO.:	Not Reg.	