

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade Name: **US Standard Fuel Tank Sealer**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the preparation: Isocyanate resin

1.3 Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

Absolute Coatings Inc.
 38 Portman Road
 New Rochelle, NY 10801
 Phone: 1-800-221-8010

1.4 Emergency telephone number:

ChemTel Inc.
 (800)255-3924, +1 (813)248-0585

2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The following classifications are applicable only to the general GHS regulations and not the specific CLP regulation: H227.

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

H227: Combustible Liquid. (General GHS and USA only)



GHS08 health hazard

Resp. Sens. 1; H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 1B; H340: May cause genetic defects.

Carc. 1B; H350: May cause cancer.

STOT RE 2; H373: May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4; H332: Harmful if inhaled.

Skin Irrit. 2; H315: Causes skin irritation.

Eye Irrit. 2; H319: Causes serious eye irritation.

Skin Sens. 1; H317: May cause an allergic skin reaction.

STOT SE 3; H335: May cause respiratory irritation.

Aquatic Chronic 3; H412: Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R40: Limited evidence of a carcinogenic effect.

Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data. The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS07 GHS08

Signal word: Danger**Hazard-determining components of labelling:**

4,4'-methylenediphenyl diisocyanate
 Solvent naphtha (petroleum), light arom.
 Polymethylene Diisocyanate Polymer
 Methylenediphenyl Diisocyanate

Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation:
 H412.

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H227.

H227: Combustible Liquid. (General GHS and USA only)

H332: Harmful if inhaled.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317: May cause an allergic skin reaction.

H340: May cause genetic defects.

H350: May cause cancer.

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

Precautionary statements

P285: In case of inadequate ventilation wear respiratory protection.

P264: Wash thoroughly after handling.

P260: Do not breathe mist/vapours/spray.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P314: Get medical advice/attention if you feel unwell.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

Additional information:

Contains isocyanates. May produce an allergic reaction.

Restricted to professional users.

Safety Data Sheet

according to 1907/2006/EC (REACH),
1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer**Hazard description:****WHMIS-symbols:**

D2A - Very toxic material causing other toxic effects.

**NFPA ratings (scale 0 - 4)**

Health = 2
Fire = 1
Reactivity = 0

HMIS-ratings (scale 0 - 4)

HEALTH	*2	
FIRE	1	
REACTIVITY	0	

Health = *2

Fire = 1

Reactivity = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

HMIS Long Term Health Hazard Substances

101-68-8	4,4'-methylenediphenyl diisocyanate
26447-40-5	Methylenediphenyl diisocyanate
9016-87-9	Polymethylene polyphenylene isocyanate

2.3 Other hazards

Ingestion: Poison!! Ingestion may be fatal or cause blindness. Cannot be made nonpoisonous.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients**3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**








	Polymer based on methylene diisocyanate ☒ Xi R36/38; ☒ Xi R43; R52 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	50-100%
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9	4,4'-methylenediphenyl diisocyanate ☒ Xn R20; ☒ Xn R42/43; ☒ Xi R36/37/38; Carc. Cat. 3 ⚠ Resp. Sens. 1, H334; STOT RE 2, H373 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-25%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4	Solvent naphtha (petroleum), light arom. ☒ Xn R65; Carc. Cat. 2 ⚠ Asp. Tox. 1, H304	<10%
CAS: 26447-40-5 EINECS: 247-714-0 Index number: 615-005-00-9	Methylenediphenyl diisocyanate ☒ Xn R20; ☒ Xn R42/43; ☒ Xi R36/37/38 Carc. Cat. 3 ⚠ Resp. Sens. 1, H334; STOT RE 2, H373 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<10%

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer

CAS: 9016-87-9	Polymethylene polyphenylene isocyanate  Xn R20-40-48/20;  Xn R42/43;  Xi R36/37/38; Carc. Cat. 3	<10%
	 Resp. Sens. 1, H334; STOT RE 2, H373  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 64742-48-9 EINECS: 265-150-3 Index number: 649-327-00-6	Naphtha (petroleum), hydrotreated heavy  Xn R65	<10%
	 Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	

Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Seek immediate medical advice.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Immediately remove contact lenses if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

4.2 Most important symptoms and effects, both acute and delayed

Asthma attacks

Nausea

Cramp

Dizziness

Headache

Profuse sweating

Disorientation

Cyanosis

Breathing difficulty

Allergic reactions

Hazards:

Danger of pneumonia.

Danger of convulsion.

Danger of disturbed cardiac rhythm.

Danger of impaired breathing.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

Contains isocyanates.

Safety Data Sheet
according to 1907/2006/EC (REACH),
1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.
 If necessary oxygen respiration treatment.
 Later observation for pneumonia and pulmonary oedema.
 Medical supervision for at least 48 hours.
 If blue colouring appears (lips, ear-lobes, finger-nails), give oxygen treatment as quickly as possible.
 Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.
 Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Alcohol resistant foam
 Fire-extinguishing powder
 Carbon dioxide
 Gaseous extinguishing agents
 Water haze or fog

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.
 Wear fully protective suit.

Additional information:

Eliminate all ignition sources if safe to do so.
 Cool endangered receptacles with water fog or haze.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Isolate area and prevent access.

Keep away from ignition sources.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Additional Spill Procedures/Neutralization: Neutralization solutions:

(1) Colorimetric Laboratories Inc. (CLI) decontamination solution.

(2) A mixture of 75% water, 20% non-ionic surfactant (e.g. Plurafac SL-62, Tergitol TMN-10) and 5% n-propanol.

(3) A mixture of 80% water, 20% non-ionic surfactant (e.g. Plurafac SL-62, Tergitol TMN-10).

(4) A mixture of 90% water, 3-8% ammonium hydroxide or concentrated ammonia, and 2% liquid detergent.

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Safety Data Sheet
according to 1907/2006/EC (REACH),
1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer**7 Handling and storage****7.1 Precautions for safe handling**

Take note of emission threshold.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Open and handle receptacle with care.

Information about fire - and explosion protection:

Keep respiratory protective device available.
Protect from heat.
Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Provide ventilation for receptacles.
Store in a cool location.
Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.
Do not store together with acids.
Store away from oxidizing agents.
Do not store together with alkalis (caustic solutions).

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Store receptacle in a well ventilated area.
Keep container tightly sealed.

7.3 Specific end use(s): No further relevant information available.**8 Exposure controls/personal protection****Additional information about design of technical facilities:** No further data; see item 7.**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****101-68-8 4,4'-methylenediphenyl diisocyanate**

PEL (USA)	Short-term value: C 0.2 mg/m ³ , C 0.02 ppm
REL (USA)	Short-term value: C 0.2* mg/m ³ , C 0.02* ppm Long-term value: 0.05 mg/m ³ , 0.005 ppm *10-min
TLV (USA)	0.051 mg/m ³ , 0.005 ppm
EL (Canada)	Short-term value: C 0.01 ppm Long-term value: 0.005 ppm Skin; S
EV (Canada)	0.005 ppm

DNELs: No further relevant information available.**PNECs:** No further relevant information available.**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer



Personal protective equipment must be selected to prevent inhalation of vapors and contact with skin and eyes. At a bare minimum, safety glasses, gloves, apron, and combination particle/vapor respirator should be worn. In some cases, supplied air, full body suits and boots will be needed.

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:



Combined Organic Vapor and Particulate Respirator are recommended for use during all processing activities.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Butyl rubber, BR

Neoprene gloves

Eye protection:

Contact lenses should not be worn.



Safety glasses

Body protection:

Full head, face and neck protection



Boots



Apron

Impervious protective clothing

Limitation and supervision of exposure into the environment

No further relevant information available.

Risk management measures

See Section 7 for additional information. No further relevant information available.

Safety Data Sheet
according to 1907/2006/EC (REACH),
1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer**9 Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Liquid
Colour:	Orange
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	406 °F / 208 °C

Flash point: 199 °F / 93 °C (Estimate)

Flammability (solid, gaseous): Not applicable.

Ignition temperature: Not determined.

Decomposition temperature: Not determined.

Self-igniting: Product is not self-igniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

Vapour pressure: Not determined.

Density: 1.06 g/cm³

Relative density: Not determined.

Vapour density: Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

Solvent content:

VOC (California): 98 g/l

Solids content: Not determined.

9.2 Other information: No further relevant information available.

10 Stability and reactivity**10.1 Reactivity****10.2 Chemical stability:****Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications

10.3 Possibility of hazardous reactions

Reacts with alcohols, amines, aqueous acids and alkalis.

Reacts with oxidizing agents.

Toxic fumes may be released if heated above the decomposition point.

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer

10.4 Conditions to avoid:

Keep away from heat and direct sunlight.

Keep ignition sources away - Do not smoke.

10.5 Incompatible materials: No further relevant information available.**10.6 Hazardous decomposition products:**

Poisonous gases/vapours

Isocyanate

Nitrogen oxides

Carbon monoxide and carbon dioxide

Hydrogen cyanide (prussic acid)

11 Toxicological information**11.1 Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:****101-68-8 4,4'-methylenediphenyl diisocyanate**

Oral	LD50	2200 mg/kg (mouse)
------	------	--------------------

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>3400 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4 h	>10,2 mg/l (rat)
------------	----------	------------------

Primary irritant effect:**On the skin:** Irritant to skin and mucous membranes.**On the eye:** Irritating effect.**Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Subacute to chronic toxicity:

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

Additional toxicological information:

Toxic and/or corrosive effects may be delayed up to 24 hours.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

Harmful

Irritant

Danger through skin adsorption.

Sensitisation:

Sensitization possible by skin contact.

Sensitization possible by inhalation and/or dermal contact.

Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

Muta. 1B, Carc. 1B

12 Ecological information**12.1 Toxicity****Aquatic toxicity:** The product contains materials that are harmful to the environment.**12.2 Persistence and degradability:** Not easily biodegradable**12.3 Bioaccumulative potential:** May be accumulated in organism

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer

12.4 Mobility in soil: No further relevant information available.

Ecotoxicological effects:**Remark:**

Due to mechanical actions of the product (e.g. agglutinations) damages may occur.
 The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.
 Harmful to fish

Additional ecological information:**General notes:**

This statement was deduced from the properties of the single components.
 Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment cannot be excluded.
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects: No further relevant information available.

13 Disposal considerations

13.1 Waste treatment methods**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

14.1 UN-Number

DOT, ADR, IMDG, IATA: N/A

14.2 UN proper shipping name

DOT, ADR, IMDG, IATA: N/A

14.3 Transport hazard class(es)

DOT, ADR, IMDG, IATA:

Class: N/A

14.4 Packing group

DOT, ADR, IMDG, IATA: N/A

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user:

Not Applicable

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable.

UN "Model Regulation":

-

Safety Data Sheet
according to 1907/2006/EC (REACH),
1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer**15 Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture United States (USA)****SARA****Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

101-68-8	4,4'-methylenediphenyl diisocyanate
9016-87-9	polymethylene polyphenylene isocyanate

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65 (California):**Chemicals known to cause cancer:**

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic Categories**EPA (Environmental Protection Agency)**

101-68-8	4,4'-methylenediphenyl diisocyanate	CBD
9016-87-9	polymethylene polyphenylene isocyanate	CBD

IARC (International Agency for Research on Cancer)

101-68-8	4,4'-methylenediphenyl diisocyanate	3
9016-87-9	polymethylene polyphenylene isocyanate	3

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Canada**Canadian Domestic Substances List (DSL)**

101-68-8	4,4'-methylenediphenyl diisocyanate
64742-48-9	Naphtha (petroleum), hydrotreated heavy
64742-95-6	Solvent naphtha (petroleum), light arom.
26447-40-5	Methylenediphenyl diisocyanate
9016-87-9	Polymethylene polyphenylene isocyanate

Canadian Ingredient Disclosure list (limit 0.1%)

101-68-8	4,4'-methylenediphenyl diisocyanate
----------	-------------------------------------

Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Safety Data Sheet
according to 1907/2006/EC (REACH),
1272/2008/EC (CLP), and GHS

Printing date: 26.06.2013

Revision: 26.06.2013

Trade Name: US Standard Fuel Tank Sealer**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.
 H319: Causes serious eye irritation.
 H332: Harmful if inhaled.
 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335: May cause respiratory irritation.
 H340: May cause genetic defects.
 H350: May cause cancer.
 H373: May cause damage to organs through prolonged or repeated exposure.
 H412: Harmful to aquatic life with long lasting effects.

R20: Harmful by inhalation.
 R36/37/38: Irritating to eyes, respiratory system and skin.
 R36/38: Irritating to eyes and skin.
 R40: Limited evidence of a carcinogenic effect.
 R42/43: May cause sensitisation by inhalation and skin contact.
 R43: May cause sensitisation by skin contact.
 R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R52: Harmful to aquatic organisms.
 R65: Harmful: may cause lung damage if swallowed.

Abbreviations and Acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 WHMIS: Workplace Hazardous Materials Information System (Canada)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent